

---

# ACOUSTICAL WALL PANELS

---

Spec Data Sheet

**Architectural Products**  
**S-2500 Noise Barrier Wall Panels**

---



High NRC and STC Ratings

Class A fire rated

Standard, designer or C.O.M.  
fabric

Acoustical wall panels by IES-2000, Inc. are the solution for areas that require noise reduction and are available in a variety of models for various applications. The S-2500 Wall Panel is manufactured specifically as a noise barrier/absorber panel that offers both superior absorption and noise blocking performance. Application for the S-2500 panels includes corporate offices, conference rooms, doctor's offices, waiting rooms, classrooms and any area where speech privacy is a concern.

The S-2500 Noise Barrier Wall Panels are the solution to speech privacy problems, providing clients the confidence that confidential conversations will not be overheard.

S-2500 Panels are constructed using 2 layers of a 6-7# PCF rigid fiberglass core between a 1 lb per square foot non-reinforced loaded vinyl noise barrier. Panels are available in 1-1/8" and 2-1/8" thickness, with a maximum size up to 4' x 10' and may be finished in custom, designer or C.O.M. fabric.

S-2500 Panels can be installed with impaling clips, top hook and construction adhesive. Due to panel weight 2.5 lb per square foot, panels must be installed from floor to ceiling. Floor molding can be re-installed after installation of S-2500 panels.



**INPLANT ENVIRO-SYSTEMS 2000, INC.**

105 W. Lynn Street, PO Box 770, St Paris, Ohio 43072  
Phone: (877)248-8640 Fax :( 937)663-0678